

CERTIFICATE OF APPROVAL – SL2



Bilock Exclusive profile double cylinder floating cam FA55A12FQ

Euro profile double cylinder

HAS BEEN APPROVED FOR

Keying systems - Security Level 2

CONDITIONS OF APPROVAL

No specific conditions of approval.

SUPPLIED BY

Australian Lock Company Pty Ltd 17 Doyle Avenue Unanderra NSW 2526

T: 02 4260 5700 F: 02 4272 4527

E: customerservice@australianlock.com.au

APPROVAL GRANTED

9/02/2016



Chair Security Construction and Equipment Committee

SECURITY EQUIPMENT RATINGS

Security Level (SL) ratings applies a 'Good, Better, Best' philosophy to security products, SL4 being the most secure through to SL1 the least secure. The following includes a brief description of the risk profile associated with each Security Level:

SL4

High Risk - Attackers are expected to have a professional level of ability to resource and implement a physical/technical attack in detail. Attackers will have a high level of expertise and will be equipped with specialist tools and equipment. Products classified at this level will offer substantial resistance against a large range of specialist attack methods for extended periods.

SL3

Medium Risk - Attackers are expected to be highly capable using a comprehensive range of non-specialist tools and equipment at their disposal. Products classified at this level will offer a moderate resistance to a range of specialist attack methods for reasonable periods.

SL₂

Low to Medium Risk - Attackers are expected to have a limited knowledge, and will have a general range of non-specialist tools and equipment. Products classified at this level will offer moderate resistance against non-specialist attacks for limited periods.

SL₁

Low Risk - Attackers are expected to have little knowledge and only the most basic tools or equipment. Products classified at this level will offer minor resistance against any attacks for very short periods.